

JMF Copper Press Fittings

JMF copper press fittings for use in plumbing or mechanical applications. Available sizes range from $\frac{1}{2}$ " through 4" in diameter. JMF press fittings are engineered to join ASTM B88 (Types K, L, M) hard drawn copper tube (1/2" through 4"). Our press fittings are approved for installations in both above and below ground applications.



MATERIALS

• Copper alloy - UNS C12200, Zero Lead silicon bronze alloy - C87710 (cast) or C87700 (machined)

FEATURED ITEMS

- Elbows
- Couplings
- Reducers
- Tees
- Caps
- Reducing Tees
- Crossovers
- Threaded Adapters

STANDARDS & SPECIFICATIONS

- IAPMO PS 117-2019 This standard covers press connections made with copper and copper alloy fittings and Type K, L and M tube and adheres to the following standards: ASME B16.3, ASME B16.18, ASTM B88, ASTM B858, ASTM D2000
- In compliance with Uniform Plumbing Code (UPC) and the National Plumbing Code of Canada

JMF COMPANY IS YOUR CONSOLIDATING SOURCE FOR copper tubing, line sets, copper fittings, push to fit, pex, ball valves, gas valves, plumbing valves, malleable fittings, steel nipples, plastic fittings, brass threaded, brass nipples, flare & compression, gas connectors, water connectors, appliance kits, cord sets and MORE.

