




**Your Single Source Solution**

## Air Conditioning and Refrigeration Grade Seamless Copper Coils

### 1/8" to 1 1/8" OD in 50' & 100' coils

- Annealed to ensure easy field installation
- Dehydrated, cleaned and capped
- Burst pressure meets or exceeds 3X maximum 410A operating pressures

O.D(inch)	Length(ft)
1/8", 1/4" to 1 1/8"	50' & 100'



Standard	Copper Alloy NO.	Chemical Composition		Mechanical Properties			
		CU%	P%	Temper	Tensile strength (Mpa)	Elongation (%)	Average
ASTM B743 & B88	C12200	>99.9	0.015 to 0.040	>060	>205	>40	>0.040

Comparison table of chemical composition & mechanical properties of the product as per domestic and foreign standards.

### Burst Pressure by O.D. (Burst pressures based upon the Barlow Formula)

1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1 1/8"
6522 PSI	4225 PSI	3125 PSI	2582PSI	2986 PSI	3401 PSI	2337 PSI

**JMF COMPANY IS YOUR CONSOLIDATING SOURCE FOR** copper tubing, line sets, copper fittings, push to fit, pex, ball valves, gas valves, plumbing valves, malleable fittings, steel nipples, plastic fittings, brass threaded, brass nipples, flare & compression, gas connectors, water connectors, appliance kits, cord sets and MORE.

