Ductless Line Sets for HVACR Applications

Ductless mini-split systems. VRF commercial systems.

Job Name	Contractor
Job Location	Wholesaler
Engineer	JMF Rep

APPLICATION - FEATURES

• Meets ASTM E84 for smoke and fire (25/50)

• R410 A Approved

• UV Resistant

• 45° Forged Flare Nuts

TECHNICAL SPECIFICATIONS

Copper Tubing: Manufactured according to ASTM B280 and meets ASTM B1003 -

Standard Specification for Seamless Copper Tube for Linesets.

Copper: No. C122200 DHP (Phosphorous deoxidized, high residual phosphorous)

Standard Back Rubber: Closed cell and light weight elastomeric material

Insulation: According to ASTM E96-00

Working Temperature: -297°F* (-183°C) to +220°F (+104°C) ASTM C534

Surface Burning Characteristics: ASTM E84 (25/50), flame

and spread index less than 25 and smoke development index less than 50

as tested according to UL 723.

Black Insulation Both Lines Insulated

 Tube Sizes
 Lengths

 1/4" - 7/8"
 10' - 100'

 1 1/8"
 10' - 50'

Insulation Wall Thickness: 3/8", 1/2" 3/4" & 1"

INSULATION R VALUES

JMF COMPANY IS YOUR CONSOLIDATING SOURCE FOR copper tubing, line sets, copper fittings, push to fit, pex, ball valves, gas valves, plumbing valves, malleable fittings, steel nipples, plastic fittings, brass threaded, brass nipples, flare & compression, gas connectors, water connectors, appliance kits, cord sets and MORE.