

Standard EZ-Pull[®] Line Sets for HVACR Applications

Split system (A/C & Heat Pump).

Job Name	Contractor
Job Location	Wholesaler
Engineer	JMF Rep

APPLICATION - FEATURES

- Meets ASTM E84 for smoke and fire (25/50)
- Rugged, anti-tear exterior allows for easier installation of the line set
- R410 A Approved
- Paintable

- Superior tear resistance
- UV Resistant
- Insulation is marked every foot
- Available in BLACK or WHITE hard shell

TECHNICAL SPECIFICATIONS

Copper Tubing: Manufactured according to ASTM B280 and meets ASTM B1003 -	EZ-Pull - Insulation (White Hard Shell):	
Standard Specification for Seamless Copper Tube for Linesets.	Uninsulated Liquid Line	
Copper: No. C122200 DHP (Phosphorous deoxidized, high residual phosphorous)	Insulated Suction Line	
Low-density Polyethylene Foam: Closed cells foam, CFC and HCFC gas free	Tube Size: 1/4" - 7/8"	
Insulation: According to ASTM E96-00		
Working Temperature: -150°F to 200°F Meets/exceeds ASTM C 1427-07	Lengths: 25', 30', 35' & 50' (See price sheet)	
Surface Burning Characteristics: UL 723, ASTM E84 (25/50), flame	Insulation Wall Thickness: 1/2" & 3/4"	
and spread index less than 25 and smoke development index less than 50		
as tested according to UL 723.		

INSULATION R VALUES

1/2" Wall - R3.3 3/4" Wall - R5.2 *R - Value calculation using a K-Factor of 0.25 BTU-in/hr-ft (2)-F @ 75ºF, 24ºC mean temp.

JMF COMPANY IS YOUR CONSOLIDATING SOURCE FOR copper tubing, line sets, copper fittings, push to fit, pex, ball valves, gas valves, plumbing valves, malleable fittings, steel nipples, plastic fittings, brass threaded, brass nipples, flare & compression, gas connectors, water connectors, appliance kits, cord sets and MORE.

